

SCHULZ

SCT 5000 FLEX

Air Compressors

The SCT 5000 Flex rotary-screw compressors are highly energy efficient, making them suitable for 24/7 operations. They offer higher performance, cost reduction, and excellent return on the investment.

Available in models from 10 to 50 hp, these compressors have an open permanent magnet motor — which facilitates maintenance — air-cooled with IP23 protection rating.

The SCT 5000 Flex rotary-screw compressors feature a variable-speed frequency inverter that controls the motor's speed and torque according to the factory's air demand. This enables reducing energy consumption and pressure fluctuations in the system.





Compressors suitable for 24/7 operation



SCT **5020** FLEX SCT **5030** FLEX SCT **5050** FLEX Models from 10 to 50 HP

Recommendation: The SCT 5000 Flex rotary-screw compressors should be installed indoors, away from weather conditions — preferably in a machine room.



KEY APPLICATIONS:

- Automotive industry
- Metalworking industry
- Maquiladora industry
- Furniture industry
- Industrial locksmithing
- Graphic industry
- Mechanical workshops



IP23 PERMANENT MAGNET MOTOR

Zero transmission loss — motor up to 8% more efficient compared to an induction motor with the same capacity



SMART CONTROL PANEL WITH MAINTENANCE ALERTS

Easy operation enhances safety and extends the compressor's lifespan



PERMANENT MAGNET MOTOR

With fewer components and high quality, it requires no preventive maintenance and offers great durability (it does not demagnetize)



VARIABLE-SPEED FREQUENCY INVERTER

High stability, reliability, and significant reduction in energy consumption



COMPACT AND WITH FEWER COMPONENTS

The compressors are affordable, simple, and easy to maintain



HIGH-PRECISION OIL FILTER

The high-efficiency filtration system ensures quality compressed air



STAINLESS STEEL TUBING

Greater durability and lifespan

MODEL	MOTOR POWER				DISPLACEMENT POWER	OPERATING PRESSURE	COMPRESSOR UNIT	TANK OUTLET TUBE	COMPRESSOR WEIGHT	DIMENSIONS (L x W x H)
	kW	HP	Hz	V	cfm	bar	Stages	Ø pol	kg	mm
SCT 5010 Flex	7,5	10	50 60	220	35	8	1	G3/4"	160	746 × 540 × 841
SCT 5020 Flex	15	20	50	220	76	8	1	G3/4"	212	920 x 640 x 1007
SCT 5030 Flex	22	30	50 60	220	113	8	1	G1 1/4"	316	980 x 780 x 1161
SCT 5050 Flex	37	50	50 60	220	212	8	1	G1 1/4"	462	1100 x 850 x 1273

SCHULZ











SCHULZ COMPRESSORES

Rua Dona Francisca, 6901 A - Distrito Industrial Fone: 47 3451.6000 - 89219-600 - Joinville - SC schulz@schulz.com.br

SCHULZ - SÃO PAULO

Av. Indianápolis, 1435 - Planalto Paulista Fone: 11 2161.1300 - 04063-002 - São Paulo - SP schulzsp@schulz.com.br



SCHULZ OF AMERICA, INC.

3500, Lake City Industrial Court - Acworth, GA 30101 Phone # (770) 529.4731 - Fax # (770) 529.4733 sales@schulzamerica.com | www.schulzamerica.com



SCHULZ - CHINA

Building no. 3 (South) - No. 19, Zheng Lang Road FengXian District - Shanghai, China ZIP CODE: 201413





